


NLGA Industrial Clears (2" & Thinner) All Species (except WRC)

Purpose Intended: Appearance

Basic Size: 8" wide x 12' long (96 surface units)



Graded from the Best Face Allowing the Reverse Face to be 1 Grade Lower
 Pieces 5" & Narrower - Best Face includes both edges;
 Pieces 6" & Wider - Best Face includes 1 edge (of your choice to your advantage)

Characteristics Permitted	B and Better Clear	C Clear	D Clear
Rate of Growth (on best end) 	Avg. 6 rings / inch	No Restriction	No Restriction
Slope of Grain 	1 in 8	1 in 6	1 in 4
Pockets <p>Pitch Streaks: (2X size of pockets)</p>	③- Very Small = $\frac{1}{8}" \times \textcircled{2}"$ or $\frac{1}{16}" \times 3"$ 3 times 2" = ⑥" total (per basic size) Any number of pockets are permitted (maximum individual length = 3") (maximum combined total length = 6")	④- Small $\frac{1}{8}" \times \textcircled{4}"$ or $\frac{1}{16}" \times 6"$ or $\frac{1}{4}" \times 2"$ 4 times 4" = ①6" total (per basic size) Any number of pockets are permitted (maximum individual length = 6") (maximum combined total length = 16")	Medium = $\frac{1}{8}" \times \textcircled{8}"$ or $\frac{1}{16}" \times 12"$ or $\frac{3}{8}" \times 4"$ ④ medium on Face ⑤ medium on Back 4 times 8" = ③2" total on Face (per Basic Size) 5 times 8" = ④0" total on Back (per Basic Size) Any number of pockets are permitted
Knots - measured by average diameter. 	Not Permitted		Face - 8 / Maximum Size = 1" / Total Sum = 4" Reverse Face - 10 / Max. Size $1\frac{1}{4}"$ / Total Sum = 5" All Knots may be of "Fixed" Quality Ignore size of knots on narrow face
Pin Holes 	3 per basic size	8 per basic size	Face: 30 / sq.ft. 38 / sq.ft. (worst area) Back: 38 / sq.ft. 47 / sq.ft. (worst area)
Holes: measured by ave. dia. 	<div>NOT</div> <div>PERMITTED</div>		Face: one, $\frac{1}{4}"$ Back: two, $\frac{1}{2}"$ Holes are linked to the basic size and are equiv. smaller.
Wane 			$\frac{1}{8}W \times \frac{1}{4}L$ or equiv. area. Never exceed $\frac{1}{4}T$ on Face; Allow 50% more on Back (i.e. $\frac{3}{8}$ Thickness)
White Specks 10% of the face area can be affected by white specks. 			Face - 25% of area
Cut Out - 1 only 			One 3", cut out permitted minimum 3' from either end in pieces that are 12' & longer.

NLGA Industrial Clears (2" & Thinner) All Species (except WRC)

Purpose Intended: Appearance